Hall Ticket Number :											ſ	
----------------------	--	--	--	--	--	--	--	--	--	--	---	--

Code: 4G554

R-14

III B.Tech. I Semester Supplementary Examinations Nov/Dec 2017

Design of Machine Elements-I

(Mechanical Engineering)

Max. Marks: 70

Time: 3 Hours

Answer all five units by choosing one question from each unit ($5 \times 14 = 70$ Marks)



- 1. a) Explain the various design considerations in machine elements.
 - b) What are the common materials used in design of machine elements? How can the properties of steel be improved?

OR

- 2. a) Explain various theories of failures.
 - b) A critical section in a solid shaft of 50 mm diameter is subjected to a twisting moment of 50 KN-m, a bending moment of 20 KN-m, and an axial compressive thrust of 60 KN. Determine the maximum value of the compressive and shear stress stresses.

UNIT–II

- 3. a) What is factor of safety? List the factors to be considered while deciding the factor of safety.
 - b) Explain how the factor of safety is determined under steady and varying loading by different methods.

OR

4. A hot rolled steel shaft is subjected to a torsional moment that varies from 330 N-m clockwise to 110 N-m counterclockwise and an applied bending moment at a critical section varies from 440 N-m to – 220 N-m. The shaft is of uniform cross-section and no keyway is present at the critical section. Determine the required shaft diameter. The material has an ultimate strength of 550 MN/m² and a yield strength of 410 MN/m². Take the endurance limit as half the ultimate strength, factor of safety of 2, size factor of 0.85 and a surface finish factor of 0.62.

UNIT-III

- 5. a) What is meant by a bolt of uniform strength? How these are obtained?
 - b) A steam engine of effective diameter 300 mm is subjected to a steam pressure of 1.5 N/mm². The cylinder head is connected by 8 bolts having yield point 330 MPa and endurance limit at 240 MPa. The bolts are tightened with an initial preload of 1.5 times the steam load. A soft copper gasket is used to make the joint leak-proof. Assuming a factor of safety 2, find the size of bolt required. The stiffness factor for copper gasket may be taken as 0.5.

OR

- 6. a) What is an eccentric loaded welded joint? Discuss the procedure for designing such a joint.
 - b) A butt welded joint with ground and flush surface is subjected to tensile load which varies from 50 kN to 100 kN. Plates are 10 mm thick. Determine the lengths of weld required for over 2, 500, 000 cycles.

UNIT–IV

- 7. a) How are the keys classified? Draw neat sketches of different types of keys and state their applications.
 - b) Design a cotter joint to connecting piston rod to the crosshead of a double acting steam engine. The diameter of the cylinder is 300 mm and the steam pressure is 1 N/mm². The allowable stresses for the material of cotter and piston rod are as follows:
 t = 50 MPa; = 40 MPa; and c = 84 MPa

OR

8. a) Design and draw a cotter joint to support a load varying from 30 kN in compression to 30 kN in tension. The material used is carbon steel for which the following allowable stresses may be used. The load is applied statically.
 Tensile stress = compressive stress = 50 MPa; shear stress = 35 MPa and crushing

I ensile stress = compressive stress = 50 MPa; shear stress = 35 MPa and crushing stress = 90 MPa.

b) What is the difference between a saddle key and a sunk key?

UNIT-V

- 9. a) Distinguish clearly, giving examples between pin, axle and shaft.
 - b) Design a bushed pin type flexible coupling to transmit 15 kW at 2000 rpm. Allowable shear stress for shafts, keys and bolts = 55 MPa. Allowable bearing stress for bolts and keys = 110 MPa. Allowable bearing pressure for rubber bush = 1 MPa.

OR

- 10. a) Discuss the function of a coupling. Give at least three practical applications.
 - b) A mild steel shaft transmits 23 kW at 200 rpm. It carries a central load of 900 N and is simply supported between the bearings 2.5 meters apart. Determine the size of the shaft, if the allowable shear stress is 42 MPa and the maximum tensile or compressive stress is not to exceed 56 MPa. What size of the shaft Will be required, if it is subjected it gradually applied loads?

Hall Ticket Number :											
----------------------	--	--	--	--	--	--	--	--	--	--	--

Code: 4G555

Max. Marks: 70

III B.Tech. I Semester Supplementary Examinations Nov/Dec 2017

Heat Transfer

(Mechanical Engineering)

Time: 3 Hours

R-14

Answer all five units by choosing one question from each unit ($5 \times 14 = 70$ Marks)

UNIT–I

- 1. a) Generate expression for temperature distribution, under 1D steady state heat conduction for cylindrical system.
 - b) What is the physical significance of the thermal diffusivity? How it is defined and what are its units?

OR

- a) What is the thickness required of a masonry wall having thermal conductivity 0.75 W/mK if the heat rate is to be 80% of the heat rate through a composite structural wall having a thermal conductivity of 0.25 W/mK and a thickness of 100 mm? Both walls are subjected to the same surface temperature difference.
 - b) What is the overall heat transfer coefficient? How is it defined and how is it related to the total thermal resistance? What are its units?

UNIT–II

- 3. a) The walls of a refrigerator are typically constructed by sandwiching a layer of insulation between sheet metal panels. Consider a wall made from fiberglass insulation of thermal conductivity 0.046 W/mK and thickness 50 mm and steel panels, each of thermal conductivity 60 W/m K and thickness 3 mm. If the wall separates refrigerated air at 4°C from ambient air at 25°C, what is the heat gain per unit surface area? Coefficients associated with natural convection at the inner and outer surfaces may be approximated as 5W/m²K.
 - b) Generate an expression for heat dissipation in straight triangular fin.

OR

- Stainless steel (AISI 304) ball bearings, which have uniformly been heated to 850°C, are hardened by quenching them in an oil bath that is maintained at 40°C. The ball diameter is 20 mm, and the convection coefficient associated with the oil bath is 1000 W/m²K.
 - a. If quenching is to occur until the surface temperature of the balls reaches 100°C, how long must the balls be kept in the oil? What is the center temperature at the conclusion of the cooling period?
 - b. If 10,000 balls are to be quenched per hour, what is the rate at which energy must be removed by the oil bath cooling system in order to maintain its temperature at 40°C?

UNIT–III

- 5. a) Generate momentum equation for hydrodynamic boundary layer over a flat plate.
 - b) A plate of length 750mm and width 250mm has been placed longitudinally in a stream of crude oil which flows with a velocity of 5m/s. if the oil has a specific gravity of 0.8 and kinematic viscosity of 1 stoke, find
 - i. Boundary layer thickness at the middle of plate.
 - ii. Shear stress at the middle of plate.
 - iii. Friction drag on one side of the plate.

OR

6. a) A horizontal, high-pressure steam pipe of 0.1-m outside diameter passes through a large room whose wall and air temperatures are 23°C. The pipe has an outside surface temperature of 165°C and an emissivity of 0.85. Estimate the heat loss from the pipe per unit length.

Use Properties: air (Tf = 367 K): k =0.0313 W/mK, Kinematic viscosity 22.8 *10⁻⁶m²/s, = 32.8 *10⁻⁶ m²/s, Pr=0.697, =2.725 *10⁻³K⁻¹.

b) How does the local convection heat or mass transfer coefficient vary with distance from the leading edge for laminar flow over a flat plate? For turbulent flow?

UNIT–IV

- 7. a) Water at the atmospheric pressure is to be boiled in the polished copper pan. The diameter of the pan is 350 mm and is kept at the 115°C.Find the following
 - i. Power of the burner.
 - ii. Rate of the evaporation in kg/h.
 - iii. Critical heat flux for these conditions.
 - b) How modes of heat transfer are associated with film boiling?

OR

- 8. a) Consider two large parallel plates, one at 1000k with the emissivity 0.8 and other is at 300k having emissivity 0.6.A radiation shield is placed between them. The shield has the emissivity as 0.1 on side facing hot plate and 0.3 on the side facing cold plate. Find percentage reduction in the radiation heat transfer as the result of radiation shield
 - b) What is Planks distribution? What is Wien's displacement law?

UNIT–V

- 9. a) Generate expression for effectiveness by NTU method for the parallel flow heat exchanger.
 - b) The overall temperature rise of the cold fluid in a cross-flow heat exchanger is 20°C and overall temperature drop of the hot-fluid is 30°C.The effectiveness of heat exchanger is 0.6. The heat exchanger area is 1 m² and overall heat transfer coefficient is 60 w/m^{2°}C. Find out the rate of the heat transfer. Assume both fluids are unmixed.

OR

- 10. a) Why are baffles used in a shell-and-tube heat exchanger?
 - b) The flow rates of the Hot and cold-water streams running through a parallel flow heat exchanger are 0.2 kg/s and 0.5 kg/s respectively. The inlet temperature on the hot and cold sides is 75°C and 20°C respectively. The exit temperature of the hot water is 45°C. If the individual heat transfer coefficient on both side are 650w/m^{2°}C.Calculate the area of the heat exchanger.

III B. Tech. I semester supplementar	
Managerial Economics a	
(Common to CE	-
. Marks: 70	Time: 3 Hours
ver all five units by choosing one questi	ion from each unit (5 x 14 = 70 Marks)
UN	IT-I
	uring Price Elasticity of demand? Given the ice elasticity using percentage and arc he good:
	OR
Briefly discuss the various methods of De	emand forecasting.
UNI	
	lly show the optimal or cost minimizing choice
Suppose in the Cobb-Douglas production	the Cobb-Douglas production function. on function, $+ > 1$, what does it imply
about the returns to scale? If + = 1 an	
UNI	T-III
Discuss in brief the short-run and long-ru market. Why do firms under Monopolistic	n equilibrium conditions under Monopolistic market operate with Excess Capacity?
	OR
Briefly discuss the various forms of busin on PPP model.	ness organizations. Write a short comment
UNI	T-IV
Define Capital. What are the different type	es of capital? Elaborate.
	OR
•	budgeting? Find out the Net Present Value Rs. 10,000/-; even cash inflow of Rs. 500/-
for a period of 2 years with 5% interest ra	
UNI	
	ifferent sections of a balance sheet? Chart
out assets and liabilities of a firm with suit	OR
What are turnover and solvency ratios? information:	Calculate current ratio from the following
Particulars	Rs
Inventories	50,000
Trade receivables	50,000
Advance tax Cash and cash equivalents	4,000 30,000
Trade payables	1,00,000
Short-term borrowings	4,000

	Page 1 of :

Answ

III B.Tech. I Semester Supplementary Examinations Nov/Dec 2017

- 2.
- 3. е
- 4. y
- 5. С
- 6. nt
- 7.
- 8. е /_
- 9. rt
- 10. g

Hall Ticket Number :

Code: 4GA51

Max.

R-14

					1		1					1	1		
Hall	Tick	et Number :												D 14	
Code	: 4G5	553												R-14	
III B.Tech. I Semester Supplementary Examinations Nov/Dec 2017 Machine Tools															
											,				
Max	Mai	rks: 70		()	Лес	nan	ICal	Engi	neei	ing)			Time: 3 Hou	rs
		er all five units	sbya	choo	osing		que *****		fron	n ead	ch ui	nit (t	5 x 14		15
							l	JNIT	-1						
1.	a)	List various t	ypes	of cł	nips.	What	facto	ors a	re res	spons	sible	for fo	ormatio	on of chips?	7M
	b)	•	ous c	uttin	g too	l mat	terial	s and	d em	phas	ize tl	neir i	mpor	tance in metal	7M
		cutting.						OR)						7 111
2.		Draw a More	shant	'e eir	ala d	liaara				ovor	occio	ne te	chov	v relationships	
۷.	a)					0				•				nt parameters	
		involved in m					2			J					7M
	b)	Write a shor	t note	e on	Tayl	or's t	ool li	fe eq	uatic	on.					7M
							ι	JNIT-	-11						
3.	a)	What are the	basi	c pa	rts of	an e	ngine	ath	e? Di	scus	s the	func	tion o	f headstock.	7M
	b)	Describe ab	out n	nulti-	spino	dle au	utom	atic I	athe	mac	hine	in de	etail.		7M
								OR							
4.		Contrast aut	oma	tic ar	nd se	mi a				nine t	ools.				14M
_	,							JNIT-							
5.	a)	Predict vario				-				-	-				7M
	b)	Explain the p	oroce	ess o	t Qu	ick re	eturn			sm in	con	text 1	io sha	iper.	7M
	,							OR							-14
6.	a)	Illustrate the					•		•						7M
	b)	Summarize	ine w	vorki	ng pr	incip				g ma	achin	e.			7M
7.	a)	How broach	ina ic	: dor		hori		INIT-		ne hr	nach	ina ·	nachi	ines	7M
1.	a) b)	Discuss the	-									-			7M
	0)			, y 01	gint	an ig l		0R	Ũ	ve y		'9 W			7 111
8.	a)	Describe the	nro	Cecc	of	enter				roce	55 W	ith a	neat	sketch	7M
0.	b)		•					•	•••					al applications.	7M
	ω,		.					JNIT-							, , , , , ,
9.	a)	List various	types	s of c	drilling	g jigs			-	l					7M
	b)	Demonstrate						. Ho	w ho	ning	and	appi	ng dif	fer	7M
	,			-		•	. 0	OR		Ŭ			-		
10.	a)	Explain the o	const	tructi	onal	featu	ures (of sp	eed a	and f	eed	units	of br	oaching tool.	7M
	b)	•						•						nd explain the	
		various type	s of o	clam	ps us	sed ir	n Jigs	sand	l fixtu	ires.					7M
							**	*							